

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1-63. (Cancelled)

64. (Currently Amended) A fuel tank comprising:

an insert having a form that defines a recessed opening;

a wall of thermoplastic material, a portion of the outside surface of the wall being overmolded on and in direct contact with the insert, which does not pierce through the wall, the overmolded wall portion ~~forming~~covering the recessed opening of the insert to form a portion in relief, on the inside of the tank, that defines an internal housing; and

an attachment separate from the insert attached to the portion in relief and at least partially received in the housing inside the tank,

wherein the insert is made of a material having a melting temperature that is higher than that of the thermoplastic material of the wall and has a form enabling mounting of the attachment in the formed internal housing.

65. (Withdrawn) A fuel tank according to claim 64, wherein the attachment is selected from the group consisting of a pipe, a filter, a pump, a fuel gauge, and a support member.

66. (Previously Presented) A fuel tank according to claim 64, wherein the attachment is a valve.

67. (Previously Presented) A fuel tank according to claim 64, wherein the portion in relief is made on a top of the wall of the tank.

68. (Previously Presented) A fuel tank according to claim 64, wherein the housing has an end wall, and the attachment comes into contact with the end wall once it has been mounted.

69. (Withdrawn) A fuel tank according to claim 64, wherein the housing is formed inside an annular wall.

70. (Withdrawn) A fuel tank according to claim 69, wherein the annular wall is interrupted.

71. (Withdrawn) A fuel tank according to claim 69, wherein the annular wall is continuous.

72. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the portion in relief comprises two tabs, the housing being formed between the tabs.

73. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the attachment is mounted in the housing along an axial direction thereof.

74. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the portion in relief has a shape selected to enable the attachment to be mounted by snap-fastening.

75. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the portion in relief has a shape selected to enable the attachment to be held by friction to the wall of the tank.

76. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein a shape of the insert is configured to reinforce the wall of the tank, limiting variations in dimensions thereof.

77. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the overmolded portion of the insert has a shape configured to guarantee effective retention in the wall of the tank.

78. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the portion in relief has an annular shape with a radially inner surface that diverges towards an outside of the tank.

79. (Canceled)

80. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the insert comprises a polyolefin.

81. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the insert comprises a metal.

82. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the insert comprises a high-density polyethylene.

83. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the wall of the tank comprises at least one layer of thermoplastic material and a layer that forms a barrier against hydrocarbons.

84. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the wall has two layers of thermoplastic material and, sandwiched between them, a layer forming a barrier against hydrocarbons.

85. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the wall of the tank has received a treatment for forming a barrier against hydrocarbons.

86. (Withdrawn-Currently Amended) A fuel tank according to claim 85, wherein the wall of the tank has received a treatment by fluorination.

87. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the wall of the fuel tank is blow molded.

88. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the wall of the fuel tank is rotomolded.

89. (Withdrawn-Currently Amended) A fuel tank according to ~~claim 65~~claim 64, wherein the wall of the fuel tank is thermoformed.

90. (Currently Amended) A fuel tank comprising:

at least one insert having a form that defines a recessed opening;

a wall of thermoplastic material, the wall having the outside surface of at least one portion covering and in direct contact with the insert, the covering portion ~~being in relief~~ and forming a portion in relief defining an internal housing covering the recessed opening of the insert; and

an attachment separate from the insert attached to the portion in relief and at least partially received in the housing and situated at least partially inside the fuel tank and not in contact with the insert,

wherein the insert is made of a material having a melting temperature that is higher than that of the thermoplastic material of the wall and has a form enabling mounting of the attachment in the formed internal housing.

91. (New) The fuel tank according to claim 90, wherein the covering portion forming the portion in relief has at least one interior peripheral wall surface that diverges toward an outside of the tank to enable mounting of the attachment.

92. (New) The fuel tank according to claim 90, wherein the portion in relief has a shape selected to enable the attachment to be mounted by snap-fastening.

93. (New) The fuel tank according to claim 90, wherein the portion in relief has a shape selected to enable the attachment to be held by friction to the wall of the tank.

94. (New) The fuel tank according to claim 64, wherein the covering portion forming the portion in relief has at least one interior peripheral wall surface that diverges toward an outside of the tank to enable mounting of the attachment.